

| TECEX | | IECEx Certificate of Conformity | |
|-----------------------------|---|------------------------------------|--|
| Certificate No.: | IECEx DEK 24.0002X | Page 2 of 3 | |
| Date of issue: | 2024-06-17 | Issue No: 0 | |
| Manufacturer: | PR Electronics A/S Lerbakken 10 8410 Rønde Denmark | | |
| Manufacturing locations: | PR Electronics A/S Lerbakken 10 8410 Rønde Denmark | | |

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

| IEC 60079-0:2017 Edition:7.0 | Explosive atmospheres - Part 0: Equipment - General requirements |
|----------------------------------|---|
| IEC 60079-11:2011 Edition:6.0 | Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i" |

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

NL/DEK/ExTR24.0002/00

Quality Assessment Report:

NL/DEK/QAR13.0017/06



IECEx Certificate of Conformity

Certificate No .:

IECEx DEK 24.0002X

Page 3 of 3

Date of issue:

Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

2024-06-17

General product information:

The panel mounted Loop Powered LCD indicator Type 5531A, 5531B is used for local readout of 4...20 mA current signals scaled directly in process units.

Electrical data

Supply and input circuit:

in type of protection intrinsic safety Ex ia IIC and Ex ic IIC only for connection to a certified intrinsically safe circuit, with the following maximum values:

U_i = 45 V; I_i = 120 mA; P_i = 0.9 W; C_i = 0 nF; L_i = 0 mH.

SPECIFIC CONDITIONS OF USE: YES as shown below:

Precautions shall be taken to minimize the risk from electrostatic discharge at module front.