

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E233311  
**Report Reference** E233311-20191125  
**Issue Date** 2019-DECEMBER-02

**Issued to:** PR ELECTRONICS A/S  
LERBAKKEN 10  
8410 ROENDE DENMARK

**This certificate confirms that  
representative samples of**

PROCESS CONTROL EQUIPMENT FOR USE IN  
HAZARDOUS LOCATIONS  
See Addendum Page

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.


**Standard(s) for Safety:**  
**Additional Information:**

See Addendum Page  
See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E233311  
**Report Reference** E233311-20191125  
**Issue Date** 2019-DECEMBER-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

**Models:**

Equipment for use in Unclassified Locations or Class I, Division 2, Groups A, B, C and D Hazardous Locations.

Solenoid/Alarm Driver Model 9203A, followed by 1 or 2, followed by A or B, followed by blank, 1 or 2, followed by -U9. May be supplied with optional display/programming module type 4501.

Associated Apparatus for use in Unclassified Locations or Class I, Division 2, Groups A, B, C and D Hazardous Locations.

Solenoid/Alarm Driver Model 9203B, followed by 1 or 2, followed by A or B, followed by blank, 1 or 2, followed by -U9, provides intrinsically safe outputs for use in Class I, Division 1, Groups A, B, C and D, Class II, Groups E, F and G, Class III Hazardous Locations when installed in accordance with manufacturer's control drawing no. 9203QU01. May be supplied with optional display/programming module type 4501.

**Standards:**


UL 913 - Standard for Intrinsically Safe Apparatus and Associated Apparatus for Use in Class I, II, and III, Division 1, Hazardous (Classified) Locations

UL121201 - Nonincendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous (Classified) Locations

CSA C22.2 NO. 60079-0 - Explosive Atmospheres - Part 0: Equipment - General Requirements

CSA C22.2 NO. 60079-11:14 - Explosive Atmospheres - Part 11: Equipment Protection by Intrinsic Safety "I"

CSA C22.2 No. 213-17 - Non-incendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Division 1 and 2 Hazardous (classified) Locations



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

